

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



15 FEB 2005

(43) International Publication Date
26 February 2004 (26.02.2004)

PCT

(10) International Publication Number
WO 2004/016340 A1

(51) International Patent Classification⁷: **B01D 53/04,**
53/26

[US/US]; 11 Miami Conservancy Road, Piqua, OH 45356 (US).

(21) International Application Number:
PCT/US2003/024898

(74) Agents: PEACOCK, Bruce, E. et al.; Wegman, Hessler & Vanderburg, Suite 200, 6055 Rockside Woods Blvd., Cleveland, OH 44131 (US).

(22) International Filing Date: 7 August 2003 (07.08.2003)

(81) Designated State (national): US.

(25) Filing Language: English

(84) Designated States (regional): European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).

(26) Publication Language: English

(30) Priority Data:
60/404,176 16 August 2002 (16.08.2002) US

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments


(71) Applicant (for all designated States except US): STANHOPE PRODUCTS COMPANY [US/US]; 379 Albert Road, P.O. Box 6003, Brookville, OH 45309-6003 (US).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(72) Inventor; and

(75) Inventor/Applicant (for US only): EVANS, John, M.

(54) Title: DESICCANT CARTRIDGE WITH SEAL



(57) **Abstract:** A desiccant cartridge (10) having a seal (12) therearound for forming a proper seal between cartridge (10) and canister (14) of a receiver/dryer or accumulator assembly includes a cup (16) extending along an axis (18) having inner wall portion (20) and outer wall portion (22) connected to transverse portion (24) to define a chamber (26) containing desiccant particles (30). Cap (70) is secured to cup (16) to secure the desiccant particles (30) inside chamber (26). Outer wall portion (22) is provided with the seal (12) that is composed of a flexible thermoplastic elastomer that is resistant to heat during welding shut of the canister (14).